

# Hladilne omare za pekarstvo

## Refrigerated bakery cabinets



| Model<br>Type | Širina x globina x višina<br>Width x depth x height<br>[mm] | Prostornina<br>Volume<br>[l] | Masa<br>Mass<br>[kg] | Temperaturno območje<br>Temperature range<br>[°C] | Priključna moč<br>Power input<br>[w] | Napajanje<br>Power supply<br>[V/hz] | Št. polic<br>No. of<br>shelves |
|---------------|---|------------------------------|----------------------|---|--------------------------------------|-------------------------------------|--------------------------------|
| BKS 600       | 780x680x2000  | 505                          | 140                  | -3/+10  | 425                                  | 230/50                              | 20                             |
| BLF 600       | 780x680x2000  | 505                          | 150                  | -5/-30  | 600                                  | 230/50                              | 20                             |
| BKS 900       | 780x960x2000  | 770                          | 170                  | -3/+10  | 640                                  | 230/50                              | 20                             |
| BLF 900       | 780x960x2000  | 770                          | 180                  | -5/-30  | 700                                  | 230/50                              | 20                             |

**KARAKTERISTIKE | FEATURES**

Ohišje izdelano iz AISI 304 | Structure made of AISI 304

Zunanji plašč sijaj | Scotchbrite polished outer coat

Avtomatsko delovanje | Fully automatic operation

Izolacija brez CFC - 70 mm | Isolation 100% CFC free - 70mm

Leva-desna vrata | Reversible doors

Samozaporna vrata | Self closing doors

Elektronska regulacija | Electronically controlled

Dinamično hlajenje | Fan assisted cooling

Zamenljiva guma na vratih | Replaceable door gasket

Nastavljive noge | Adjustable feet

Ključavnica | Lock

Zaobljeni koti za enostavno čiščenje | Internal rounded corners for easy cleaning

Delovanje do temperature okolice +43 °C | High ambient temperature operation up to +43°C

Zamenljiva hladilna enota | Removable compact refrigerating unit

Primerne za pladnje 60 x 40 | Suitable for bakery norm trays 60 x 40

Primerne za pladnje 60 x 80 (Model 900) | Suitable for bakery norm trays 60 x 80

Avtomatsko električno odtaljevanje | Automatic electric defrost

**NOTRANJA OPREMA | FITTING**

20 parov nastavljivih in odstranljivih L profilov |

20 pairs of adjustable and removable L supports

**OPCIJE | OPTIONS**

Kolesca | Castors

Izvedba brez agregata | Remote unit

Steklena vrata pri BKS modelu | Glass door at BKS models

R290 okolju prijazen plin | R290 environment-friendly gas

Plastificirana rešetka 600 x 800 mm | Shelve 600 x 800mm

Nožno pedalo | Foot pedal



nožno pedalo

foot pedal



zamenljiva guma

replaceable door gasket



kolesca

castors




zaobljeni vogali

rounded corners



zamenljiv agregat

removable refrigerating unit



L profili

L supports