
Hladilne omare GN2/1

Refrigerated cabinets GN2/1





Model Type	Širina x globina x višina Width x depth x height [mm]	Prostornina Volume [l]	Masa Mass [kg]	Temperaturno območje Temperature range [°C]	Priključna moč Power input [w]	Napajanje Power supply [V/hz]	Št. polic No. of shelves
CM 700 SS	710x800x2000	650	150	-2/+8	425	230/50	4
CN 700 SS	710x800x2000	650	162	-18/-24	600	230/50	4
CM 1400 SS	1420x800x2000	1300	230	-2/+8	530	230/50	8
CN 1400 SS	1420x800x2000	1300	245	-18/-24	700	230/50	8
CM/CM 700 SS	710x800x2000	650	165	+2/+10, -2/+8	540	230/50	4
CM/CN 700 SS	710x800x2000	650	165	-2/+8, -18/-22	720	230/50	4
CN/CN 700 SS	710x800x2000	650	165	-18/-22, -18	850	230/50	4
CM/CN 1400 SS	1420x800x2000	1300	254	-2/+8, -18/-22	1025	230/50	8
CM 700 SS SV*	710x800x2000	650	160	-2/+8	425	230/50	4
CN 700 SS SV*	710x800x2000	650	170	-18/-22	700	230/50	4
CM 1400 SS SV*	1420x800x2000	1300	250	-2/+8	640	230/50	8
CN 1400 SS SV*	1420x800x2000	1300	270	-18/-22	900	230/50	8

* za temperaturo okolice 32 °C / for ambient temperature of 32°C

C..... Omara GN2/1 | Cabinet GN2/1

700/1400... Model | Model

SS..... Nerjaveča pločevina AISI 304 | Stainless steel AISI 304

SV..... Steklena vrata | Glass door

2D..... Dvojna vrata po višini | Two vertical doors

RU..... Oddvojeni agregat | Remote unit

M..... Temperaturno območje -2°/-8° | Temperature range -2°/-8°

N..... Temperaturno območje -18°/-24° | Temperature range 18°/-24°

KARAKTERISTIKE | FEATURES

Ohišje izdelano iz AISI 304 | Structure made of AISI 304
Zunanji plašč sijaj | Scotchbrite polished outer coat
Avtomatsko delovanje | Fully automatic operation
Izolacija brez CFC - 70 mm | Isolation 100% CFC free - 70mm
Leva-desna vrata | Reversible doors
Samozaporna vrata | Self closing doors
Elektronska regulacija | Electronically controlled
Dinamično hlajenje | Fan assisted cooling
Zamenljiva guma na vratih | Replaceable door gasket
Nastavljive noge | Adjustable feet
Ključavnica | Lock
Zaobljeni koti za enostavno čiščenje | Rounded corners for easy cleaning
Delovanje do temperature okolice +43 °C | High ambient temperature operation up to +43°C
Zamenljiva hladilna enota | Removable compact refrigerating unit

NOTRANJA OPREMA | FITTING


Nastavljive in odstranljive nosilne letve | Adjustable and removable shelf supports
Plastificirane rešetke | Plastic coated shelves
Notranja osvetlitev | Internal lighting
Ključavnica | Lock

OPCIJE | OPTIONS

Zračni filter kondenzatorja | Condenser air filter
Možnost visoke ali nizke vlage (CM modeli) | Low/high humidity mode (CM models)
RU verzija | RU version
RF rešetke | SS shelves
LED osvetlitev | LED lighting
R290 okolju prijazen plin | R290 environment-friendly gas

DODATNA OPREMA | ACCESSORIES

Kolesca | Castors
Nožno pedalo | Foot pedal
Pekarski set | Confectionary set



RF rešetka

SS shelves



zamenljiva guma

replaceable door gasket



kolesca

castors



zaobljeni vogali

rounded corners



nožno pedalo

foot pedal



zamenljiv agregat

removable refrigerating unit