

ALASKA INTEGRAL R290 OPEN FRONT 3M2	71	100	120	150	180	240	300	360
	Cabinets composition with perspex divider							
<b>DIMENSIONS</b>								
Width x depth	710x790	960x790	1250x790	1510x790	1856x790	2435x790	2955x790	3622x790
Height	1950							
Internal width	640	896	1186	1446	1792	2371	2891	3583
<b>TECHNICAL SPECIFICATIONS</b>								
Volume	320 l	444 l	588 l	717 l	889 l	1176 l	1434 l	1777 l
Surface area	1.47 m <sup>2</sup>	2.05 m <sup>2</sup>	2.71 m <sup>2</sup>	3.31 m <sup>2</sup>	4.10 m <sup>2</sup>	5.43 m <sup>2</sup>	6.63 m <sup>2</sup>	8.20 m <sup>2</sup>
TDA (total display area)	0.76 m <sup>2</sup>	1.05 m <sup>2</sup>	1.39 m <sup>2</sup>	1.69 m <sup>2</sup>	2.09 m <sup>2</sup>	2.77 m <sup>2</sup>	3.38 m <sup>2</sup>	4.18 m <sup>2</sup>
<b>TECHNICAL DATA</b>								
Power supply	230Vac - 50Hz							
Input power (W)	1052	1068	1217	1369	2132	2x1217	2x1369	3x1217
Current drawn (A)	5,7	6,1	7,5	7,2	12,1	2 x 7.5	2 x 7.2	3 x 7.5
Power cords (n)	1	1	1	1	1	2	2	3
Cooling rate (W)	1400	1810	2166	2640	3620	2x2166	2x2640	3x2166
Refrigerant gas	R290/140 g	R290/150 g	R290/2x140 g	R290/2x150 g	R290/2x150 g	R290/4x140 g	R290/4x150 g	R290/6x140 g
Energy consumption 24h (kWh)	10.43	12.39	14.75	16.85	21.18	2x14.75	2x16.85	3x14.75
Noise level	52 dB	56 dB	61 dB	60 dB	63.5 dB	74.5 dB	76 dB	78 dB
<b>TEMPERATURE</b>								
Range	+3°C/+5°C - 25°C / 60%							
<b>WEIGHT</b>								
Net	176 kg	198 kg	239 kg	277 kg	320 kg	410 kg	498 kg	618 kg
<b>ENERGY CLASS</b>								
	E	E	E	E	F	2xE	2xE	3xE
<b>EEl</b>								
	59.3	60.4	61.7	62.6	68.4	2x61.7	2x62.6	3x61.7
<b>ENERGY CLASS PANORAMIC ENDS</b>								
	D	D	D	D	E	2xD	2xD	3xD
<b>EEl PANORAMIC ENDS</b>								
	37.8	40.7	43.6	45.7	51.7	2x43.6	2x45.7	3x43.6