

ALASKA REMOTE OPEN FRONT 3M2	71	100	120	150	180	240	300	360
DIMENSIONS								
Width x depth	710x790	960x790	1250x790	1510x790	1856x790	2435x790	2955x790	3647x790
Height	1950							
Internal width	640	896	1186	1446	1792	2371	2891	3583
TECHNICAL SPECIFICATIONS								
Volume	320 l	444 l	588 l	717 l	889 l	1176 l	1434 l	1777 l
Surface area	1.47 m ²	2.05 m ²	2.71 m ²	3.31 m ²	4.10 m ²	5.43 m ²	6.63 m ²	8.20 m ²
TDA (total display area)	0.76 m ²	1.05 m ²	1.39 m ²	1.69 m ²	2.09 m ²	2.77 m ²	3.38 m ²	4.18 m ²
TECHNICAL DATA								
Power supply	230Vac - 50Hz							
Input power (W)	20	32	45	47	60	84	90	116
Current drawn (A)	0,1	0,2	0,3	0,3	0,4	0,6	0,6	0,8
Power cords (n)	1	1	1	1	1	1	1	1
Cooling rate (W)	1307	1307	1755	1997	2604	3510	3994	5208
Refrigerant gas	*	*	*	*	*	*	*	*
Energy consumption 24h (kWh)	8.87	11.09	13.65	15.95	18.97	24.1	28.72	34.75
Noise level	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB
TEMPERATURE								
Range	+3°C/+5°C - 25°C / 60%							
WEIGHT								
Net	136 kg	158 kg	171 kg	206 kg	234 kg	299 kg	354 kg	411 kg
ENERGY CLASS								
	E	E	E	F	F	F	F	F
EEl								
	55.4	59.5	62.8	65.2	67.4	70.2	72.1	73.6
ENERGY CLASS PANORAMIC ENDS								
	D	D	D	D	E	E	E	E
EEl PANORAMIC ENDS								
	35.4	40	44.3	47.6	51	55.5	58.7	61.8