

ALASKA SLIM INTEGRAL R290 OPEN FRONT 3M2	71	100	120	150	180	240	300	360
	Cabinets composition with perspex divider							
DIMENSIONS								
Width x depth	710x635	960x635	1250x635	1510x635	1856x635	2435x635	2955x635	3622x635
Height	1950							
Internal width	640	896	1186	1446	1792	2371	2891	3583
TECHNICAL SPECIFICATIONS								
Volume	246 l	343 l	455 l	555 l	688 l	910 l	1110 l	1376 l
Surface area	0.97 m ²	1.35 m ²	1.79 m ²	2.18 m ²	2.70 m ²	3.58 m ²	4.37 m ²	5.40 m ²
TDA (total display area)	0.76 m ²	1.05 m ²	1.39 m ²	1.69 m ²	2.09 m ²	2.77 m ²	3.38 m ²	4.18 m ²
TECHNICAL DATA								
Power supply	230Vac - 50Hz							
Input power (W)	1054	1066	1205	1364	2128	2x1205	2x1364	3x1205
Current drawn (A)	5,8	6,2	7,6	7,3	12,3	2 x 7.6	2 x 7.3	3 x 7.6
Power cords (n)	1	1	1	1	1	2	2	3
Cooling rate (W)	1400	1810	2166	2640	3620	2x2166	2x2640	3x2166
Refrigerant gas	R290/140 g	R290/150 g	R290/2x140 g	R290/2x150 g	R290/2x150 g	R290/4x140 g	R290/4x150 g	R290/6x140 g
Energy consumption 24h (kWh)	9.59	11.41	13.59	15.53	19.51	2x13.59	2x15.53	3x13.59
Noise level	52 dB	56 dB	61 dB	60 dB	63.5 dB	74.5 dB	76 dB	78 dB
TEMPERATURE								
Range	+3°C/+5°C - 25°C / 60%							
WEIGHT								
Net	152 kg	179 kg	209 kg	241 kg	281 kg	362 kg	450 kg	590 kg
ENERGY CLASS								
	E	E	E	E	E	2xE	2xE	3xE
EEL								
	54.5	55.7	56.9	57.7	63	2x56.9	2x57.7	3x56.9
ENERGY CLASS PANORAMIC ENDS								
	D	D	D	D	E	2xD	2xD	3xD
EEL PANORAMIC ENDS								
	40.3	42.8	45.2	46.9	52.5	2x45.2	2x46.9	3x45.2