

ALASKA SLIM REMOTE OPEN FRONT 3M2	71	100	120	150	180	240	300	360
DIMENSIONS								
Width x depth	710x635	960x635	1250x635	1510x635	1856x635	2435x635	2955x635	3647x635
Height	1950							
Internal width	640	896	1186	1446	1792	2371	2891	3583
TECHNICAL SPECIFICATIONS								
Volume	246 l	343 l	455 l	555 l	688 l	910 l	1110 l	1376 l
Surface area	0.97 m ²	1.35 m ²	1.79 m ²	2.18 m ²	2.70 m ²	3.58 m ²	4.37 m ²	5.40 m ²
TDA (total display area)	0.76 m ²	1.05 m ²	1.39 m ²	1.69 m ²	2.09 m ²	2.77 m ²	3.38 m ²	4.18 m ²
TECHNICAL DATA								
Power supply	230Vac - 50Hz							
Input power (W)	20	32	45	47	60	84	90	116
Current drawn (A)	0,1	0,2	0,3	0,3	0,4	0,6	0,6	0,8
Power cords (n)	1	1	1	1	1	1	1	1
Cooling rate (W)	1223	1307	1755	1997	1997	3510	3994	3994
Refrigerant gas	*	*	*	*	*	*	*	*
Energy consumption 24h (kWh)	10.1	10.22	12.58	14.71	17.49	22.23	26.49	32.05
Noise level	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB
TEMPERATURE								
Range	+3°C/+5°C - 25°C / 60%							
WEIGHT								
Net	127 kg	143 kg	173 kg	208 kg	236 kg	301 kg	345 kg	510 kg
ENERGY CLASS								
	E	E	E	E	E	E	F	F
E EI								
	63.1	54.8	57.9	60.1	62.2	64.7	66.5	67.9
ENERGY CLASS PANORAMIC ENDS								
	D	D	D	D	E	E	E	E
E EI PANORAMIC ENDS								
	46.7	42.1	46	48.9	51.8	55.6	58.3	60.7