

<b>ALASKA VBN SLIM REMOTE OPEN FRONT 3M2</b>	<b>71</b>	<b>100</b>	<b>120</b>	<b>150</b>	<b>180</b>	<b>240</b>	<b>300</b>	<b>360</b>
<b>DIMENSIONS</b>								
Width x depth	710x635	960x635	1250x635	1510x635	1856x635	2435x635	2955x635	3647x635
Height	2095							
Internal width	640	896	1186	1446	1792	2371	2891	3583
<b>TECHNICAL SPECIFICATIONS</b>								
Volume	290 l	405 l	538 l	656 l	813 l	1076 l	1312 l	1627 l
Surface area	1.16 m <sup>2</sup>	1.61 m <sup>2</sup>	2.14 m <sup>2</sup>	2.61 m <sup>2</sup>	3.22 m <sup>2</sup>	4.28 m <sup>2</sup>	5.22 m <sup>2</sup>	6.45 m <sup>2</sup>
TDA (total display area)	0.91 m <sup>2</sup>	1.26 m <sup>2</sup>	1.67 m <sup>2</sup>	2.04 m <sup>2</sup>	2.52 m <sup>2</sup>	3.34 m <sup>2</sup>	4.07 m <sup>2</sup>	5.05 m <sup>2</sup>
<b>TECHNICAL DATA</b>								
Power supply	230Vac - 50Hz							
Input power (W)	20	32	45	47	60	84	90	116
Current drawn (A)	0,1	0,2	0,3	0,3	0,4	0,6	0,6	0,8
Power cords (n)	1	1	1	1	1	1	1	1
Cooling rate (W)	1307	1307	1755	1997	2604	3510	3994	5208
Refrigerant gas	*	*	*	*	*	*	*	*
Energy consumption 24h (kWh)	7.49	9.88	13.63	17	20.58	27.26	34.01	41.17
Noise level	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB	45 dB
<b>TEMPERATURE</b>								
Range	+3°C/+5°C - 25°C / 60%							
<b>WEIGHT</b>								
Net	127 kg	143 kg	173 kg	208 kg	236 kg	301 kg	345 kg	510 kg
<b>ENERGY CLASS</b>								
	D	D	E	E	E	F	F	F
<b>EEl</b>								
	43	48	56.1	61.5	64.2	69	73.6	74.8
<b>ENERGY CLASS PANORAMIC ENDS</b>								
	C	D	D	D	E	E	E	F
<b>EEl PANORAMIC ENDS</b>								
	30.9	36.1	43.8	49.4	53	58.8	64.2	66.6