



SC 500GSS	LSC 235	LSC 280	TCBD 68	TCBD 98	MOD.
	vetrocamera / insulated glass	vetrocamera / insulated glass	vetrocamera / insulated glass	vetrocamera / insulated glass	TIPOLOGIE PORTE - DOORS TYPE TYPOLOGIES DE PORTES - TÜRENTYPOLOGIE
					
920x520x1872	515x485x1650	515x485x1850	428x386x930	428x386x1150	DIMENSIONI ESTERNE LxPxH mm EXTERNAL DIMENSIONS LxPxH mm DIMENSIONS EXTERIEURES LxPxH mm AUBENABMESSUNGEN LxPxH mm
855x424x1437	473x405x1135	473x405x1338	350x350x535	350x350x760	DIMENSIONI INTERNE LxPxH mm INTERNAL DIMENSIONS LxPxH mm DIMENSIONS INTERNE LxPxH mm INNENABMESSUNGEN LxPxH mm
975x570x2035	555x525x1790	555x525x1990	488x446x970	488x446x1195	DIMENSIONI IMBALLO PACKAGE DIMENSIONS DIMENSIONS DE L'EMBALLAGE ABMESSUNGEN DES KARTONS
120	96	107	33	38	PESO NETTO KG NET WEIGHT KG POIDS NET KG NETTO GEWICHT KG
INOX - ALLUMINIO INOX - ALUMINIUM	LAMIERA VERNICIATA - PLASTICA - VETRO PAINTED TINPLATE - PLASTIC - GLASS	LAMIERA VERNICIATA - PLASTICA - VETRO PAINTED TINPLATE - PLASTIC - GLASS	LAMIERA VERNICIATA - PLASTICA - VETRO PAINTED TINPLATE - PLASTIC - GLASS	LAMIERA VERNICIATA - PLASTICA - VETRO PAINTED TINPLATE - PLASTIC - GLASS	MATERIALE DI COSTRUZIONE CONSTRUCTION MATERIAL MATERIEL DE CONSTRUCTION BAUMATERIAL
490	235	280	58	98	CAPACITA' LT. CAPACITY LT. CAPACITE' LT. KAPAZITÄT LT.
45	DOPPIO VETRO DOUBLE GLAZING	DOPPIO VETRO DOUBLE GLAZING	DOPPIO VETRO DOUBLE GLAZING	DOPPIO VETRO DOUBLE GLAZING	ISOLAMENTO mm INSULATION mm ISOLATION mm ISOLATION mm
STATICA STATIC	VENTILATA VENTILATED	VENTILATA VENTILATED	VENTILATA VENTILATED	VENTILATA VENTILATED	REFRIGERAZIONE REFRIGERATION REFRIGERATION KÜHLUNG
+2°C + 8°C	+2°C + 8°C	+2°C + 8°C	+2°C + 8°C	+2°C + 8°C	TEMPERATURA °C TEMPERATURE °C TEMPERATURE °C TEMPERATUR °C
ELETTRONICO ELECTRONIC	ELETTRONICO ELECTRONIC	ELETTRONICO ELECTRONIC	ELETTRONICO ELECTRONIC	ELETTRONICO ELECTRONIC	CONTROLLO TEMPERATURA TEMPERATURE CONTROL CONTRÔLE DE LA TEMPERATURE TEMPERATURKONTROLLE
A SOSTA STOP COMPRESSOR	A SOSTA STOP COMPRESSOR	A SOSTA STOP COMPRESSOR	A SOSTA STOP COMPRESSOR	A SOSTA STOP COMPRESSOR	TIPO DI SBRINAMENTO DEFROSTING TYPE TYPE DE DEGIVRAGE ENTFROSTEN TYP
+33°C 60%HR	+28°C 60%HR	+28°C 60%HR	+28°C 60%HR	+28°C 60%HR	MAX TEMPERATURA/UMIDITÀ AMBIENTE MAXIMUM ROOM TEMPERATURE/HUMIDITY TEMPÉRATURE/HUMIDITÉ MAXIMALES DE L'AMBIANCE HÖCHSTRAUMTEMPERATUR/ HÖCHSTRAUMFEUCHTIGKEIT
AUTOMATICO AUTOMATIC	AUTOMATICO AUTOMATIC	AUTOMATICO AUTOMATIC	AUTOMATICO AUTOMATIC	AUTOMATICO AUTOMATIC	EVAPORAZIONE ACQUA CONDENSA CONDENSE WATER EVAPORATION EVAPORATION DE L'EAU DE CONDENSATION VERDAMPFUNG DES KONDENSATWASSER
R 134a	R134a	R134a	R134a	R134a	TIPO DI REFRIGERANTE REFRIGERATION TYPE TYPE DE REFRIGERATION KÜHLUNGSTYP
510	240	240	164	200	POTENZA ASSORBITA - POWER W PUISSANCE - LEISTUNG W
230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ	TENSIONE - POWER SUPPLY V BRANCHEMENT - STROMVERSORGUNG V
NO	NO	NO	NO	NO	INVERSIONE PORTA - DOOR INVERSION INVERSION DE LA PORTE - TÜRUMKEHR
LED	LED	LED	LED	LED	LUCE INTERNA - INTERNAL LIGHT LUMIERE INTERIEURE - INNENLICHT
n 8 griglie / grills 400x337	n 3 griglie / grills 400x410	n 4 griglie / grills 400x410	n 3 griglie / grills 340x335	n 4 griglie / grills 340x335	ACCESSORI IN DOTAZIONE STANDARD EQUIPMENT ACCESSOIRES EN DOTATION ZUBEHÖRAUSSTATTUNG